

Sixty6 P 110 | 80W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded and Sheet Aluminium

Primary Lens -

Primary Reflector White Optics

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC, Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 68.5W

System Power Watts 78.7W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|--------------|------|-------|-------|-------|--------|---------|
| | Sixty6 P 110 | 80W | WW27K | CRI80 | 96° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL |
|--------------|------|-------|----------|-------|-------|-------|--------|---------------|
| Sixty6 P 110 | 80W | 9601 | 122 | 2700K | WW27K | 96° | White | Non Dimmable |
| | | 9916 | 126 | 3000K | WW30K | | Black | Dali Dimmable |
| | | 10546 | 134 | 4000K | NW40K | | Custom | Casambi |
| | | 10782 | 137 | 5700K | CW57K | | | |
| Sixty6 P 110 | 80W | | | WW27K | CRI80 | 96° | SWH | On/Off |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 42V-48Vdc/1550mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable