

Twinline P OPD 120 | 28W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 23.8W

System Power Watts 27.4W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|---------------------------|------------|--------------|--------------|-------------|------------|---------------|
| | Twinline P OPD 120 | 28W | WW27K | CRI80 | 110° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | | | |
|---------------------------|------------|-------|----------|--------------|--------------|--------------|-------------|---------------|--------------|---------------|-------------|
| Twinline P OPD 120 | 28W | 2219 | 81 | 2700K | WW27K | CRI80 | 110° | White | Non Dimmable | On/Off | |
| | | 2274 | 83 | 3000K | WW30K | | | CRI90 | Black | Dali Dimmable | DDIM |
| | | 2384 | 87 | 4000K | NW40K | | | | Custom | Casambi | CBTM |
| | | 2439 | 89 | 5700K | CW57K | | | | | | |
| | | | | 2700K-5700K | TW | | | | | | |
| Twinline P OPD 120 | 28W | | | WW27K | CRI80 | 110° | SWH | On/Off | | | |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/700mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable