

Twinline P MPD 120 | 20W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 17.1W

System Power Watts 19.6W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|---------------------------|------------|--------------|--------------|------------|------------|---------------|
| | Twinline P MPD 120 | 20W | WW27K | CRI80 | 72° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | | CRI | ANGLE | FINISH | | CONTROL | |
|---------------------------|------------|-------|----------|--------------|--------------|--------------|------------|------------|------------|---------------|---------------|
| Twinline P MPD 120 | 20W | 1509 | 77 | 2700K | WW27K | CRI80 | 72° | White | SWH | Non Dimmable | On/Off |
| | | 1548 | 79 | 3000K | WW30K | CRI90 | | Black | SBL | Dali Dimmable | DDIM |
| | | 1627 | 83 | 4000K | NW40K | | | Custom | CSM | Casambi | CBTM |
| | | 1666 | 85 | 5700K | CW57K | | | | | | |
| | | | | 2700K-5700K | TW | | | | | | |
| Twinline P MPD 120 | 20W | | | WW27K | | CRI80 | 72° | SWH | | On/Off | |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable