

Twinline P MPD 240 | 56W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 48.0W

System Power Watts 55.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Twinline P MPD 240	56W	WW27K	CRI80	72°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Twinline P MPD 240	56W	4140	75	2700K	WW27K	CRI80	72°	White	SWH	Non Dimmable	On/Off
		4250	77	3000K	WW30K	CRI90		Black	SBL	Dali Dimmable	DDIM
		4471	81	4000K	NW40K			Custom	CSM	Casambi	CBTM
		4582	83	5700K	CW57K						
				2700K-5700K	TW						
Twinline P MPD 240	56W			WW27K		CRI80	72°	SWH	On/off		



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/1400mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable