
ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3 | Tilt

Optional: Bluetooth | Dimmable | Tunable White | Warm to Dim | CRI 90

ProLed 75 PF | 18W





Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt Yes

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote


LED Power Watts 15.3W

System Power Watts 17.6W

Operating Voltage Vin 220-240Vac

Power Factor p.f. >0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted Cree COB LED 36Vdc/450mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	ProLed 75 PF	**18W**	**2700K**	**CRI80**	**26°(MD)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
ProLed 75 PF	**18W**	1426	81	2700K	**2700K**	**CRI80**	26°(MD)	**26°**	White	**SWH**	Non Dimmable	**On/Off**
		1478	84	3000K	**3000K**	CRI90	44°(WD)	**44°**	Black	**SBL**	Phase Dimmable	**PDIM**
		1549	88	4000K	**4000K**		58°(VWD)	**58°**			Dali Dimmable	**DDIM**
		1584	90	5700K	**5700K**						Bluetooth Dimmable	**BTTM**
											Casambi	**CBTM**
ProLed 75 PF	**18W**			**2700K**		**CRI80**	**26°(MD)**		**SWH**		**On/Off**	