

Roa Deep MPD 120 | 20W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt -

Swivel -

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 16.9W

System Power Watts 19.4W

Operating Voltage Vin 220-240Vac


Power Factor p.f. >0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Roa Deep MPD 120	20W	2700K	CRI80	93°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Roa Deep MPD 120	20W	1610	83	2700K	2700K	CRI80	93°	White	SWH	Non Dimmable	On/Off
		1668	86	3000K	3000K	CRI90		Black	SBL	Dali Dimmable	DDIM
		1746	90	4000K	4000K			Custom	CSM	Casambi	CBTM
		1785	92	5700K	5700K						
				2700K-5700K	TW						
Roa Deep MPD 120	20W			2700K		CRI80	93°	SWH		On/Off	



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI