

# Roa Deep MPD 240 | 80W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt -

Swivel -

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 68.9W

System Power Watts 79.2W

Operating Voltage  $V_{in}$  220-240Vac

Power Factor p.f. >0.95



## Light Distribution

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type -

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/2000mA

## Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Roa Deep MPD 240	80W	WW27K	CRI80	93°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Roa Deep MPD 240	80W	6257	79	2700K	WW27K	CRI80	93°	White	SWH	Non Dimmable	On/Off
		6415	81	3000K	WW30K	CRI90		Black	SBL	Dali Dimmable	DDIM
		6732	85	4000K	NW40K			Custom	CSM	Casambi	CBTM
		6890	87	5700K	CW57K						
				2700K-5700K	TW						
Roa Deep MPD 240	80W			WW27K		CRI80	93°	SWH		On/off	