
ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3

Optional: Dimmable | Tunable White | CRI 90 | Uplight

Nexus 135 SDS R MPD 180 | 88W





Note : S- Soft , D- Dark

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector PC Black Cover

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote


LED Power Watts 75.1W

System Power Watts 86.3W

Operating Voltage Vin 220V- 240V/50-60Hz

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/1500mA(S) + 700mA(D)

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nexus 135 SDS R MPD 180	**88W**	**WW27K**	**CRI80**	**83°(S)+53°(D)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Nexus 135 SDS R MPD 180	**88W**	6227	72	2700K	**WW27K**	**CRI80**	83°(S)+53°(D)	White	**SWH**	Non Dimmable	**On/Off**
		6400	74	3000K	**WW30K**	CRI90		Black	**SBL**	Dali Dimmable	**DDIM**
		6745	78	4000K	**NW40K**			Custom	**CSM**	Casambi	**CBTM**
		6918	80	5700K	**CW57K**						
				2700K-5700K	**TW**						
Nexus 135 SDS R MPD 180	**88W**			**WW27K**		**CRI80**	**83°(S)+53°(D)**	**SWH**		**On/Off**	