

Nexus 135 SDS R MPD 240 | 120W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector PC Black Cover

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 103W

System Power Watts 118.4W


Operating Voltage Vin 220V- 240V/50-60Hz

Power Factor p.f. > 0.95



Note : S- Soft , D- Dark

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 32V-36Vdc/2100mA(S) + 1050mA(D)

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Nexus 135 SDS R MPD 240	120W	WW27K	CRI80	83°(s)+53°(D)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Nexus 135 SDS R MPD 240	120W	8560	72	2700K	WW27K	CRI80	83°(s)+53°(D)	White SWH Non Dimmable On/Off
		8796	74	3000K	WW30K	CRI90		Black SBL Dali Dimmable DDIM
		9270	78	4000K	NW40K			Custom CSM Casambi CBTM
		9507	80	5700K	CW57K			
				2700K-5700K	TW			
Nexus 135 SDS R MPD 240	120W			WW27K	CRI80	83°(s)+53°(D)	SWH	On/Off

