

# Ampio S | 15W

## Product Reference

Environment Indoor

Installation Ceiling Surface

## Construction & Materials

Housing Aluminium Extrusion

Primary Lens PMMA Opal


Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -



## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling


## Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

## Light Distribution



## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 12.4W

System Power Watts 14.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Ampio S</b>	<b>15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>90°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Ampio S</b>	<b>15W</b>	1179	83	2700K	<b>WW27K</b>	<b>90°</b>	White	Non Dimmable
		1221	86	3000K	<b>WW30K</b>		Black	Phase Dimmable
		1278	90	4000K	<b>NW40K</b>			Dali Dimmable
		1306	92	5700K	<b>CW57K</b>			Bluetooth Dimmable
				2700K-5700K	<b>TW</b>			Casambi
<b>Ampio S</b>	<b>15W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>90°</b>	<b>SWH</b>	<b>On/Off</b>

