

# Stellar 105 | 50W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector PMMA Clear

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 42.9W


System Power Watts 49.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid Power LED array 33V-36Vdc/1200mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Stellar 105</b>	<b>50W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>44°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Stellar 105</b>	<b>50W</b>	4141	84	2700K	<b>WW27K</b>	<b>CRI80</b>	White <b>SWH</b> Black <b>SBL</b> Custom <b>CSM</b>	Non Dimmable <b>On/Off</b>
		4289	87	3000K	<b>WW30K</b>	CRI90		Phase Dimmable <b>PDIM</b>
		4486	91	4000K	<b>NW40K</b>			Dali Dimmable <b>DDIM</b>
		4585	93	5700K	<b>CW57K</b>			Bluetooth Dimmable <b>BTTM</b> Casambi <b>CBTM</b>
<b>Stellar 105</b>	<b>50W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>44°</b>	<b>SWH</b>	<b>On/Off</b>