

# iSkim 100 | 12W

## Product Reference

Environment Indoor

Installation Ceiling Surface

## Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Voltage Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Remote

LED Power Watts 12.0W


System Power Watts -

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Cree LED 23V-24Vdc

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>iSkim 100</b>	<b>12W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>88°x 32°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
<b>iSkim 100</b>	<b>12W</b>	1140	95	2700K	<b>WW27K</b>	88°x 32°	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		1176	98	3000K	<b>WW30K</b>		Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		1236	103	4000K	<b>NW40K</b>				Dali Dimmable	<b>DDIM</b>
		1260	105	5700K	<b>CW57K</b>				Bluetooth Dimmable	<b>BTTM</b>
				2700K-5700K	<b>TW</b>				Casambi	<b>CBTM</b>
<b>iSkim 100</b>	<b>12W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>88°x 32°</b>	<b>SWH</b>	<b>On/Off</b>		