A B B Y

572mm

BEFERENCE FROM

500mm

55mm

Adjustable Suspensio Kit

90mm

Flute 50 P AGB 57 | 10W

Product Reference

Environment Indoor	
Installation Ceiling Suspended	

Construction & Materials

Housing Aluminium Extrusion
Primary Lens -
Primary Reflector PC metallised
Secondary Reflector Black Raster – ABS
Body Finish White,Black
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam	Direction	Fixed	Asymmetric
Dogini	Dirootion	1 1/10/04	Adyniniocito

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 8.9W
System Power Watts 10.2W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95



Light Distribution



LED Technolog	1
Binning 3 Step	MacAdam
LED Life Time @	L70/B10 >50000 hours
Colour Renderi	ng (CRI) CRI80,CRI90
Led Type SMD h	nigh power
LED Fitted Cree	LED 33V-36Vdc/250m/

Optional PDIM, DDIM, CASAMBI, Non Dimmable

Standard Switchable On/Off

Ordering Details

Code Example.	Flute 50 P AGB 57		WW27K		<u> </u>	SWH	On/Off
Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Flute 50 P AGB 57	10W	1000	98	2700K	WW27K	CRI80	34°	White	SWH	Non Dimmable	On/Off
		1030	101	3000K	WW30K	CRI90		Black	SBL	Phase Dimmable	PDIM
		1081	106	4000K	NW40K					Dali Dimmable	DDIM
		1102	108	5700K	CW57K					Casambi	CBTM
Flute 50 P AGB 57	10W			WW27K		CRI80	34°	SWH		On/Off	

Abby Lighting & Switchgear Limited 802 A, Fortune Terraces, New Link Road, Opp City Mall, Andheri West, Mumbai - 400053, India.

Abby reserves the right to discontinue any product from its collection at any time whatsover and without prior notice