

Flute 50 P AGB 57 | 10W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Aluminium Extrusion

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 8.9W

System Power Watts 10.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|--------------------------|------------|--------------|--------------|------------|------------|---------------|
| | Flute 50 P AGB 57 | 10W | WW27K | CRI80 | 34° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL |
|--------------------------|------------|-------|----------|--------------------|--------------|------------|------------------|----------------------------|
| Flute 50 P AGB 57 | 10W | 1000 | 98 | 2700K WW27K | CRI80 | 34° | White SWH | Non Dimmable On/Off |
| | | 1030 | 101 | 3000K WW30K | CRI90 | | Black SBL | Phase Dimmable PDIM |
| | | 1081 | 106 | 4000K NW40K | | | | Dali Dimmable DDIM |
| | | 1102 | 108 | 5700K CW57K | | | | Casambi CBTM |
| Flute 50 P AGB 57 | 10W | | | WW27K | CRI80 | 34° | SWH | On/Off |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Cree LED 33V-36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable