

# Flute 50 P AGB 227 | 40W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Aluminium Extrusion

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 35.5W

System Power Watts 40.8W

Operating Voltage Vin 220-240 Vac



Power Factor p.f. > 0.95

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Flute 50 P AGB 227</b>	<b>40W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>34°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
<b>Flute 50 P AGB 227</b>	<b>40W</b>	3998	98	2700K	<b>WW27K</b>	<b>CRI80</b>	34°	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		4121	101	3000K	<b>WW30K</b>	CRI90		Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		4325	106	4000K	<b>NW40K</b>					Dali Dimmable	<b>DDIM</b>
		4406	108	5700K	<b>CW57K</b>					Casambi	<b>CBTM</b>
<b>Flute 50 P AGB 227</b>	<b>40W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>34°</b>	<b>SWH</b>	<b>On/Off</b>			



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Cree LED 33V-36Vdc/1000mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable