

# Flute 50 P AGW 57 | 10W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Aluminium Extrusion

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector White Raster – ABS

Body Finish White,Black

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 8.9W

System Power Watts 10.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

## Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Flute 50 P AGW 57</b>	<b>10W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>34°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Flute 50 P AGW 57</b>	<b>10W</b>	1000	98	2700K	<b>WW27K</b>	34°	White	Non Dimmable
		1030	101	3000K	<b>WW30K</b>		Black	Phase Dimmable
		1081	106	4000K	<b>NW40K</b>			Dali Dimmable
		1102	108	5700K	<b>CW57K</b>			Casambi
<b>Flute 50 P AGW 57</b>	<b>10W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>34°</b>	<b>SWH</b>	<b>On/Off</b>



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted Cree LED 33V-36Vdc/250mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable