

iNline S 60 | 20W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included




Mounting Integral

LED Power Watts 17.0W

System Power Watts 19.55W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-38Vdc/500mA

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|--------------------|------------|--------------|--------------|-------------|------------|---------------|
| | iNline S 60 | 20W | WW27K | CRI80 | 103° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | | |
|--------------------|------------|-------|----------|--------------|--------------|--------------|------------|---|----------------------------|---------------------------|
| iNline S 60 | 20W | 1975 | 101 | 2700K | WW27K | CRI80 | 103° | White SWH Black SBL Custom CSM | Non Dimmable On/Off | |
| | | 2033 | 104 | 3000K | WW30K | | | | CRI90 | Dali Dimmable DDIM |
| | | 2151 | 110 | 4000K | NW40K | | | | | Casambi CBTM |
| | | 2229 | 114 | 5700K | CW57K | | | | | |
| | | | | 2700K-5700K | TW | | | | | |
| iNline S 60 | 20W | | | WW27K | CRI80 | 103° | SWH | On/Off | | |