

u4yA 30 | 15W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Spun Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal, Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 12.9W

System Power Watts 14.8W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|----------------|------------|--------------|--------------|------------|------------|---------------|
| | u4yA 30 | 15W | WW27K | CRI80 | 80° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | | |
|----------------|------------|-------|----------|--------------|--------------|------------|------------|---------------|----------------|---------------|
| u4yA 30 | 15W | 1051 | 71 | 2700K | WW27K | 80° | White | SWH | Non Dimmable | On/Off |
| | | 1080 | 73 | 3000K | WW30K | | Black | SBL | Phase Dimmable | PDIM |
| | | 1140 | 77 | 4000K | NW40K | | Custom | CSM | Dali Dimmable | DDIM |
| | | 1184 | 80 | 5700K | CW57K | | | | Casambi | CBTM |
| u4yA 30 | 15W | | | WW27K | CRI80 | 80° | SWH | On/Off | | |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 20V-24Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable