

# Outline Wallgrazer 120 | 20W

## Product Reference

Environment Outdoor

Installation Ceiling Surface

## Construction & Materials

Housing Extruded Aluminium

Primary Lens Polycarbonate

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 16.9W


System Power Watts 19.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/500mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name                          | Watt       | CCT          | CRI          | Angle           | Finish    | Control       |
|---------------|-------------------------------|------------|--------------|--------------|-----------------|-----------|---------------|
|               | <b>Outline Wallgrazer 120</b> | <b>20W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>91°x 30°</b> | <b>AL</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                   | WATT | LUMEN | EFFICACY | CCT   | CRI          | ANGLE        | FINISH             | CONTROL        |               |
|------------------------|------|-------|----------|-------|--------------|--------------|--------------------|----------------|---------------|
| Outline Wallgrazer 120 | 20W  | 2134  | 110      | 2700K | <b>WW27K</b> | <b>CRI80</b> | Anodised Aluminium | Non Dimmable   | <b>On/Off</b> |
|                        |      | 2192  | 113      | 3000K | <b>WW30K</b> | CRI90        |                    | Phase Dimmable | <b>PDIM</b>   |
|                        |      | 2309  | 119      | 4000K | <b>NW40K</b> |              | Dali Dimmable      | <b>DDIM</b>    |               |
|                        |      | 2347  | 121      | 5700K | <b>CW57K</b> |              | Bluetooth          | <b>BTTM</b>    |               |
|                        |      |       |          |       |              | 2700K-5700K  | <b>TW</b>          |                | Dimmable      |

| NAME                              | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE           | FINISH    | CONTROL       |
|-----------------------------------|------------|-------|----------|--------------|--------------|-----------------|-----------|---------------|
| <b>Outline Wallgrazer<br/>120</b> | <b>20W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> | <b>91°x 30°</b> | <b>AL</b> | <b>On/Off</b> |

Abby Lighting & Switchgear Limited 802 A, Fortune Terraces, New Link Road, Opp City Mall, Andheri West, Mumbai - 400053, India.

frontdesk@abbylighting.com, +91 9833645212

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

www.abbylighting.com