

Outline Wallgrazer 120 | 28W

Product Reference

Environment Outdoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 23.1W


System Power Watts 26.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|-------------------------------|------------|--------------|--------------|----------------|-----------|---------------|
| | Outline Wallgrazer 120 | 28W | WW27K | CRI80 | 91°x30° | AL | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | | CRI | ANGLE | FINISH | CONTROL | | |
|-------------------------------|------------|-------|----------|--------------|--------------|----------------|-----------|--------------------|-----------|--------------------|---------------|
| Outline Wallgrazer 120 | 28W | 2846 | 107 | 2700K | WW27K | CRI80 | 91°x30° | Anodised Aluminium | AL | Non Dimmable | On/Off |
| | | 2926 | 110 | 3000K | WW30K | CRI90 | | | | Phase Dimmable | PDIM |
| | | 3086 | 116 | 4000K | NW40K | | | | | Dali Dimmable | DDIM |
| | | 3139 | 118 | 5700K | CW57K | | | | | Bluetooth Dimmable | BTTM |
| | | | | 2700K-5700K | TW | | | | | Casambi | CBTM |
| Outline Wallgrazer 120 | 28W | | | WW27K | CRI80 | 91°x30° | AL | On/Off | | | |

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

frontdesk@abbylighting.com, +91 9833645212

www.abbylighting.com