

Outline Wallwash 120 | 20W

Product Reference

Environment Outdoor

Installation Ceiling Surface

Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector -

Body Finish Anodised Aluminium

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt -

Swivel -

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 16.7W


System Power Watts 19.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. >0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Outline Wallwash 120	20W	WW27K	CRI80		AL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH	CONTROL		
Outline Wallwash 120	20W	1920	100	2700K	WW27K	CRI80		Anodised Aluminium	AL	Non Dimmable	On/Off
		1978	103	3000K	WW30K	CRI90			Phase Dimmable	PDIM	
		2074	108	4000K	NW40K				Dali Dimmable	DDIM	
		2112	110	5700K	CW57K				Bluetooth Dimmable	BTTM	
				2700K-5700K	TW				Casambi	CBTM	
Outline Wallwash 120	20W			WW27K	CRI80		AL		On/Off		

Abby reserves the right to discontinue any product from its collection at any time whatsoever and without prior notice

frontdesk@abbylighting.com, +91 9833645212

www.abbylighting.com