

# iSoft Wash R 168 | 30W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC

Antiglare Baffle -

## Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 25.1W


System Power Watts 28.8W

Operating Voltage Vin -

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 34-36Vdc/750mA

## Controls

Standard Switchable On/Off

Optional DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

| Code Example: | Name                    | Watt       | CCT          | CRI          | Angle | Finish     | Control       |
|---------------|-------------------------|------------|--------------|--------------|-------|------------|---------------|
|               | <b>iSoft Wash R 168</b> | <b>30W</b> | <b>WW27K</b> | <b>CRI80</b> |       | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                    | WATT       | LUMEN | EFFICACY | CCT          | CRI          | ANGLE        | FINISH     | CONTROL            |               |
|-------------------------|------------|-------|----------|--------------|--------------|--------------|------------|--------------------|---------------|
| <b>iSoft Wash R 168</b> | <b>30W</b> | 2189  | 76       | 2700K        | <b>WW27K</b> | <b>CRI80</b> | White      | Non Dimmable       | <b>On/Off</b> |
|                         |            | 2246  | 78       | 3000K        | <b>WW30K</b> | CRI90        | Black      | Dali Dimmable      | <b>DDIM</b>   |
|                         |            | 2362  | 82       | 4000K        | <b>NW40K</b> |              | Custom     | Bluetooth Dimmable | <b>BTTM</b>   |
|                         |            | 2419  | 84       | 5700K        | <b>CW57K</b> |              |            | Casambi            | <b>CBTM</b>   |
| <b>iSoft Wash R 168</b> | <b>30W</b> |       |          | <b>WW27K</b> | <b>CRI80</b> |              | <b>SWH</b> | <b>On/Off</b>      |               |