

Slate D/I | 52W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded and Die Cast Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 45.8W

System Power Watts 52.6W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Slate D/I	52W	WW27K	CRI80	91°	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Slate D/I	52W	4734		2700K	WW27K	91°	White	SWH	Non Dimmable	On/Off
		4892		3000K	WW30K		Black	SBL	Dali Dimmable	DDIM
		5155		4000K	NW40K		Custom	CSM	Casambi	CBTM
		5260		5700K	CW57K					
				2700K-5700K	TW					
Slate D/I	52W			WW27K	CRI80	91°	SWH	On/Off		



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted -

Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable