

## Slate D/I | 52W

### Product Reference

Environment Indoor

Installation Ceiling Suspended

### Construction & Materials

Housing Extruded and Die Cast Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Microprismatic

Antiglare Baffle -

### Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 45.8W

System Power Watts 52.6W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

### Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Slate D/I</b>	<b>52W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>91°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL			
<b>Slate D/I</b>	<b>52W</b>	4734		2700K	<b>WW27K</b>	91°	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>	
		4892		3000K	<b>WW30K</b>		CRI90	Black	<b>SBL</b>	Dali Dimmable	<b>DDIM</b>
		5155		4000K	<b>NW40K</b>			Custom	<b>CSM</b>	Casambi	<b>CBTM</b>
		5260		5700K	<b>CW57K</b>						
				2700K-5700K	<b>TW</b>						
<b>Slate D/I</b>	<b>52W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>91°</b>	<b>SWH</b>	<b>On/Off</b>			



### Light Distribution

### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted -

### Controls

Standard Switchable On/Off

Optional DDIM,CASAMBI,Non Dimmable