

# iPro R 56 | 16W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Black Raster - PC, White Raster - PC

Body Finish White, Black, Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 13.4W

System Power Watts 15.4W

Operating Voltage Vin 220-240 Vac



Power Factor p.f. > 0.95

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>iPro R 56</b>	<b>16W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>52°(WD)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>iPro R 56</b>	<b>16W</b>	1740	113	2700K	<b>WW27K</b>	<b>CRI80</b>	52°(WD) 52°(WD)	Non Dimmable <b>On/Off</b>
		1786	116	3000K	<b>WW30K</b>	CRI90	82°(VWD)	Dali Dimmable <b>DDIM</b>
		1879	122	4000K	<b>NW40K</b>			Bluetooth Dimmable <b>BTTM</b>
		1910	124	5700K	<b>CW57K</b>			Casambi <b>CBTM</b>
				2700K-5700K	<b>TW</b>			
<b>iPro R 56</b>	<b>16W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>52°(WD)</b>	<b>SWH</b>	<b>On/Off</b>



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80, CRI90

Led Type SMD

LED Fitted Samsung Mid power LED array 39-42Vdc/350mA

## Controls

Standard Switchable On/Off

Optional DDIM, BTTM, CASAMBI, Non Dimmable