

# iWash P 112 | 32W

## Product Reference

Environment Indoor

Installation Ceiling Suspended

## Construction & Materials

Housing Extruded Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector Black Raster – PC, White Raster – PC

Body Finish White, Black, Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Integral

LED Power Watts 26.6W


System Power Watts 30.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80, CRI90

Led Type SMD

LED Fitted Samsung Mid power LED array 39-42Vdc/700mA

## Controls

Standard Switchable On/Off

Optional DDIM, CASAMBI, Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>iWash P 112</b>	<b>32W</b>	<b>WW27K</b>	<b>CRI80</b>		<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>iWash P 112</b>	<b>32W</b>	2815	92	2700K	<b>WW27K</b>	<b>CRI80</b>	White	Non Dimmable <b>On/Off</b>
		2907	95	3000K	<b>WW30K</b>	CRI90	Black	Dali Dimmable <b>DDIM</b>
		3091	101	4000K	<b>NW40K</b>		Custom	Casambi <b>CBTM</b>
		3152	103	5700K	<b>CW57K</b>			
				2700K-5700K	<b>TW</b>			
<b>iWash P 112</b>	<b>32W</b>			<b>WW27K</b>	<b>CRI80</b>		<b>SWH</b>	<b>on/Off</b>