

ZuG OPD P 180 | 30W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector Aluminium White Painted

Secondary Reflector -

Body Finish White,Black

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 25.6W


System Power Watts 29.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid Power LED array 33V-36Vdc/750mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|---------------|------|-------|-------|-------|--------|---------|
| | ZuG OPD P 180 | 30W | WW27K | CRI80 | 105° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | |
|---------------|------|-------|----------|-------|-------|-------------|--------|-----------|------------------------|
| ZuG OPD P 180 | 30W | 2411 | 82 | 2700K | WW27K | CRI80 | 105° | White SWH | Non Dimmable On/Off |
| | | 2470 | 84 | 3000K | WW30K | CRI90 | | Black SBL | Phase Dimmable PDIM |
| | | 2587 | 88 | 4000K | NW40K | | | | Dali Dimmable DDIM |
| | | 2646 | 90 | 5700K | CW57K | | | | Bluetooth Dimmable BTM |
| | | | | | | 2700K-5700K | TW | | |
| ZuG OPD P 180 | 30W | | | WW27K | CRI80 | 105° | SWH | On/Off | |

