

ABBY LIGHTING

220V 240V 50/60Hz | CRI 80 | IP20 | MacAdam Step 3

Optional: Bluetooth | Dimmable | Tunable White | CRI 90

ZuG OPD P 240 | 40W





Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector Aluminium White Painted

Secondary Reflector -

Body Finish White,Black

Diffuser Premium high-transmission opal

Antiglare Baffle Black,White,Custom

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral


LED Power Watts 34.1W

System Power Watts 39.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid Power LED array 33V-36Vdc/1000mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	ZuG OPD P 240	**40W**	**WW27K**	**CRI80**	**105°**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
ZuG OPD P 240	**40W**	3214	82	2700K	**WW27K**	**CRI80**	105°	White	**SWH**	Non Dimmable	**On/Off**
		3293	84	3000K	**WW30K**	CRI90		Black	**SBL**	Phase Dimmable	**PDIM**
		3450	88	4000K	**NW40K**					Dali Dimmable	**DDIM**
		3528	90	5700K	**CW57K**					Bluetooth Dimmable	**BTTM**
				2700K-5700K	**TW**					Casambi	**CBTM**
ZuG OPD P 240	**40W**			**WW27K**		**CRI80**	**105°**	**SWH**		**On/Off**	