

ABBY LIGHTING

50/60Hz | CRI 80 | IP20 | L80B10 >50,000h | MacAdam Step 3

Optional: Dimmable | Warm to Dim | CRI 90

Bling F | 5W





Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Milled Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote


LED Power Watts 3.5W

System Power Watts 4.4W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.5

Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/130mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Bling F	**5W**	**WW27K**	**CRI80**	**33°(MD)**	**SWH**	**On/Off**

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Bling F	**5W**	330	75	2700K	**WW27K**	**CRI80**	33°(MD)	**33°(MD)**	White	**SWH**	Non Dimmable	**On/Off**
		352	80	3000K	**WW30K**	CRI90			Black	**SBL**	Phase Dimmable	**PDIM**
		374	85	4000K	**NW40K**				Custom	**CSM**	Dali Dimmable	**DDIM**
		383	87	5700K	**CW57K**						Casambi	**CBTM**
				Warm to Dim	**W2D**							
Bling F	**5W**			**WW27K**		**CRI80**	**33°(MD)**		**SWH**		**On/Off**	