

Dark Knight DL 5 | 14W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster – ABS

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 12.2W

System Power Watts 14.0W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Dark Knight DL 5	14W	WW27K	CRI80		SWH	On/off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Dark Knight DL 5	14W	994	71	2700K	WW27K	CRI80	White	Non Dimmable	On/Off
		1036	74	3000K	WW30K	CRI90	Black	Phase Dimmable	PDIM
		1092	78	4000K	NW40K		Custom	Dali Dimmable	DDIM
		1120	80	5700K	CW57K			Bluetooth Dimmable	BTTM
							Casambi	CBTM	
Dark Knight DL 5	14W			WW27K	CRI80		SWH	On/Off	



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/350mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable