

Hoopla Soft 80 | 55W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Extruded Aluminium

Primary Lens -

Primary Reflector White Optics

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Opal PC

Antiglare Baffle -

Thermal Management

Heat Sink Material Extruded Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Integral

LED Power Watts 47.2W


System Power Watts 54.2W

Operating Voltage V_{in} 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Osram/Samsung Mid power LED array 33V-36Vdc/1400mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Hoopla Soft 80	55W	WW27K	CRI80	110°	SWH	On/off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Hoopla Soft 80	55W	4553	84	2700K	WW27K	CRI80	110°	White SWH	Non Dimmable On/Off	
		4715	87	3000K	WW30K			CRI90	Black SBL	Phase Dimmable PDIM
		4932	91	4000K	NW40K				Custom CSM	Dali Dimmable DDIM
		5041	93	5700K	CW57K					Bluetooth Dimmable BTTM
				2700K-5700K	TW					Casambi CBTM
Hoopla Soft 80	55W			WW27K	CRI80	110°	SWH	On/off		