

# iPoint | 5W

## Product Reference

Environment Indoor  
Installation Ceiling Recess

## Construction & Materials

Housing Milled Aluminium  
Primary Lens -  
Primary Reflector PC metallised  
Secondary Reflector -  
Body Finish White,Black,Custom  
Diffuser -  
Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium  
Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed  
Tilt No  
Swivel No

## Electrical System


Driven with Constant Current Driver  
Input Voltage/Hz 220V- 240V/50-60Hz  
Control Gear Included  
Mounting Remote  
LED Power Watts 3.4W  
System Power Watts 4.2W  
Operating Voltage Vin 220-240 Vac  
Power Factor p.f. > 0.5

## Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>iPoint</b>	<b>5W</b>	<b>WW27K</b>	<b>CR180</b>	<b>16°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
<b>iPoint</b>	<b>5W</b>	328	78	2700K	<b>WW27K</b>	<b>CR180</b>	16°(SS)	<b>25°(MD)</b>	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		349	83	3000K	<b>WW30K</b>	CR190	25°(MD)		Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		370	88	4000K	<b>NW40K</b>		40°(WD)		Custom	<b>CSM</b>	Dali Dimmable	<b>DDIM</b>
		378	90	5700K	<b>CW57K</b>							Casambi
<b>iPoint</b>	<b>5W</b>			<b>WW27K</b>		<b>CR180</b>	<b>16°(SS)</b>		<b>SWH</b>		<b>On/Off</b>	



## Light Distribution



## LED Technology

Binning 3 Step MacAdam  
LED Life Time @ L70/B10 >50000 hours  
Colour Rendering (CRI) CR180,CR190  
Led Type COB  
LED Fitted CREE COB LED 9Vdc/350mA

## Controls

Standard Switchable On/Off  
Optional PDIM,DDIM,CASAMBI,Non Dimmable