

iPoint | 5W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing Milled Aluminium
Primary Lens -
Primary Reflector PC metallised
Secondary Reflector -
Body Finish White,Black,Custom
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed
Tilt No
Swivel No

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 3.4W
System Power Watts 4.2W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.5

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	iPoint	5W	WW27K	CRI80	16°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
iPoint	5W	328	78	2700K	WW27K	CRI80	16°(SS)	25°(MD)	White	SWH	Non Dimmable	On/Off
		349	83	3000K	WW30K	CRI90	25°(MD)		Black	SBL	Phase Dimmable	PDIM
		370	88	4000K	NW40K		40°(WD)		Custom	CSM	Dali Dimmable	DDIM
		378	90	5700K	CW57K							Casambi
iPoint	5W			WW27K		CRI80	16°(SS)		SWH		On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type COB
LED Fitted CREE COB LED 36Vdc/130mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,CASAMBI,Non Dimmable