

# Look Around SR | 10W

## Product Reference

Environment Indoor

Installation Semi Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 8.8W


System Power Watts 10.1W

Operating Voltage  $V_{in}$  220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Look Around SR	10W	WW27K	CRI80	18°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Look Around SR	10W	970	96	2700K	WW27K	CRI80	18°(SS) 26°(MD)	Non Dimmable On/Off
		1010	100	3000K	WW30K	CRI90	26°(MD)	Phase Dimmable PDIM
		1081	107	4000K	NW40K		36°(WD)	Dali Dimmable DDIM
		1101	109	5700K	CW57K			Bluetooth Dimmable BTTM
					2700K-5700K	TW		
				Warm to Dim	W2D			
Look Around SR	10W			WW27K	CRI80	18°(SS)	SWH	On/Off