

Look Straight Down | 15W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 12.4W

System Power Watts 14.3W

Operating Voltage V_{in} 220-240 Vac





Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Look Straight Down	15W	WW27K	CRI80	18°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Look Straight Down	15W	1249	87	2700K	WW27K	CRI80	18°(SS)	White SWH Non Dimmable On/Off	
		1301	91	3000K	WW30K	CRI90	26°(MD)	Black SBL Phase Dimmable PDIM	
		1392	97	4000K	NW40K		36°(WD)	Custom CSM Dali Dimmable DDIM	
		1418	99	5700K	CW57K			Bluetooth Dimmable BTTM	
				2700K-5700K	TW				Casambi CBTM
					Warm to Dim	W2D			
Look Straight Down	15W			WW27K	CRI80	18°(SS)	SWH	On/Off	



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable