

iKapp 63 | 22W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 18.4W

System Power Watts 21.1W

Operating Voltage V_{in} 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	iKapp 63	22W	WW27K	CRI80	20°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL		
iKapp 63	22W	1730	82	2700K	WW27K	CRI80	20°(SS)	25°(MD)	White	SWH	Non Dimmable	On/Off	
		1836	87	3000K	WW30K	CRI90	25°(MD)		Black	SBL	Phase Dimmable	PDIM	
		1983	94	4000K	NW40K		30°(WD)		Custom	CSM	Dali Dimmable	DDIM	
		2047	97	5700K	CW57K							Bluetooth Dimmable	BTTM
				2700K-5700K	TW							Casambi	CBTM
				Warm to Dim	W2D								
iKapp 63	22W			WW27K		CRI80	20°(SS)		SWH		On/Off		



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable