

iKapp 63 | 22W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 18.4W

System Power Watts 21.1W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details


| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|-----------------|------------|--------------|--------------|----------------|------------|---------------|
| | iKapp 63 | 22W | WW27K | CRI80 | 20°(SS) | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | |
|-----------------|------------|-------|----------|--------------|--------------|----------------|------------|--------------------|---------|
| iKapp 63 | 22W | 1730 | 82 | 2700K | WW27K | CRI80 | White | Non Dimmable | |
| | | 1836 | 87 | 3000K | WW30K | CRI90 | Black | Phase Dimmable | |
| | | 1983 | 94 | 4000K | NW40K | | Custom | Dali Dimmable | |
| | | 2047 | 97 | 5700K | CW57K | | | Bluetooth Dimmable | |
| | | | | 2700K-5700K | TW | | | | Casambi |
| | | | | Warm to Dim | W2D | | | | |
| iKapp 63 | 22W | | | WW27K | CRI80 | 20°(SS) | SWH | On/Off | |



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable