

iKapp Wash 35 | 5W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 3.7W


System Power Watts 4.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.5



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/130mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|----------------------|-----------|--------------|--------------|-------|------------|---------------|
| | iKapp Wash 35 | 5W | WW27K | CRI80 | | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | |
|----------------------|-----------|-------|----------|--------------|--------------|--------------|------------|----------------|---------------|
| iKapp Wash 35 | 5W | 365 | 87 | 2700K | WW27K | CRI80 | White | Non Dimmable | On/Off |
| | | 391 | 93 | 3000K | WW30K | CRI90 | Black | Phase Dimmable | PDIM |
| | | 416 | 99 | 4000K | NW40K | | Custom | Dali Dimmable | DDIM |
| | | 424 | 101 | 5700K | CW57K | | | Casambi | CBTM |
| iKapp Wash 35 | 5W | | | WW27K | CRI80 | | SWH | On/Off | |