

iKapp Wash 63 | 22W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 18.4W


System Power Watts 21.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	iKapp Wash 63	22W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
iKapp Wash 63	22W	1823	86	2700K	WW27K		White	SWH	Non Dimmable	On/Off
		1929	91	3000K	WW30K		Black	SBL	Phase Dimmable	PDIM
		2078	98	4000K	NW40K		Custom	CSM	Dali Dimmable	DDIM
		2141	101	5700K	CW57K				Bluetooth Dimmable	BTTM
				2700K-5700K	TW				Casambi	CBTM
					Warm to Dim		W2D			
iKapp Wash 63	22W			WW27K	CRI80		SWH	On/Off		