

# Luke 75 2Way | 2X30W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Adjustable

Tilt Yes

Swivel Yes

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included





Mounting Remote

LED Power Watts 2x25.5W

System Power Watts 2x29.3W

Operating Voltage  $V_{in}$  220-240 Vac

Power Factor p.f. > 0.95



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/700mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTMM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Luke 75 2Way	2X30W	WW27K	CRI80	16°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Luke 75 2Way	2X30W	2x2637	90	2700K	WW27K	CRI80	16°(SS)	White SWH Non Dimmable On/Off
		2x2813	96	3000K	WW30K	CRI90	22°(MD)	Black SBL Phase Dimmable PDIM
		2x3018	103	4000K	NW40K		32°(WD)	Custom CSM Dali Dimmable DDIM
		2x3194	109	5700K	CW57K			Bluetooth Dimmable BTMM
				2700K-5700K	TW			Casambi CBTM
				Warm to Dim	W2D			
Luke 75 2Way	2X30W			WW27K	CRI80	16°(SS)	SWH	On/Off