

Ovo Carbon S 50 | 8W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 7.5W

System Power Watts 8.6W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

Ordering Details




Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Ovo Carbon S 50	8W	WW27K	CRI80	20°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Ovo Carbon S 50	8W	550	64	2700K	WW27K	CRI80	20°(SS)	White SWH Non Dimmable On/Off
		585	68	3000K	WW30K	CRI90	28°(MD)	Black SBL Phase Dimmable PDIM
		620	72	4000K	NW40K		36°(WD)	Custom CSM Dali Dimmable DDIM
		637	74	5700K	CW57K			Casambi CBTM
Ovo Carbon S 50	8W			WW27K	CRI80	20°(SS)	SWH	On/Off



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/180mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable