

Xo Pro 75 | 24W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing Aluminium
Primary Lens PMMA
Primary Reflector -
Secondary Reflector -
Body Finish White,Black,Custom
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable
Tilt Yes
Swivel Yes

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 19.7W
System Power Watts 22.6W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Xo Pro 75	24W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Xo Pro 75	24W	2283	101	2700K	WW27K	CRI80	White	Non Dimmable	On/Off
		2350	104	3000K	WW30K	CRI90	Black	Phase Dimmable	PDIM
		2463	109	4000K	NW40K		Custom	Dali Dimmable	DDIM
		2509	111	5700K	CW57K			Bluetooth Dimmable	BTTM
					2700K-5700K	TW			Casambi
				Warm to Dim	W2D				
Xo Pro 75	24W			WW27K	CRI80	22°(SS)	SWH	On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type COB
LED Fitted Cree COB LED 36Vdc/600mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable