

Xo Pro 75 | 30W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing Aluminium
Primary Lens PMMA
Primary Reflector -
Secondary Reflector -
Body Finish White,Black,Custom
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable
Tilt Yes
Swivel Yes

Electrical System





Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 25.5W
System Power Watts 29.3W
Operating Voltage V_{in} 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Xo Pro 75	30W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Xo Pro 75	30W	2725	93	2700K	WW27K	CRI80	22°(SS)	White	SWH	Non Dimmable	On/Off
		2813	96	3000K	WW30K	CRI90	41°(MD)	Black	SBL	Phase Dimmable	PDIM
		2959	101	4000K	NW40K		56°(WD)	Custom	CSM	Dali Dimmable	DDIM
		3018	103	5700K	CW57K					Bluetooth Dimmable	BTTM
				2700K-5700K	TW						Casambi
				2700K-5700K	W2D						
				Warm to Dim							
Xo Pro 75	30W			WW27K		CRI80	22°(SS)	SWH		On/Off	



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type COB
LED Fitted Cree COB LED 36Vdc/750mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable