

Xo Pro 75 | 36W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing Aluminium
Primary Lens PMMA
Primary Reflector -
Secondary Reflector -
Body Finish White,Black,Custom
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable
Tilt Yes
Swivel Yes

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 31.4W
System Power Watts 36.1W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Xo Pro 75	36W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Xo Pro 75	36W	2996	83	2700K	WW27K	CRI80	White	Non Dimmable	
		3105	86	3000K	WW30K	CRI90	Black	Phase Dimmable	
		3249	90	4000K	NW40K		Custom	Dali Dimmable	
		3321	92	5700K	CW57K			Bluetooth Dimmable	
					2700K-5700K	TW		Casambi	BTM
					Warm to Dim	W2D			CBTM
Xo Pro 75	36W			WW27K	CRI80	22°(SS)	SWH	On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CRI80,CRI90
Led Type COB
LED Fitted Cree COB LED 36Vdc/900mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable