

# Tiny AR | 12W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt Yes

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 10.8W

System Power Watts 12.4W

Operating Voltage Vin 220-240 Vac



Power Factor p.f. > 0.95

## Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Tiny AR</b>	<b>12W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>50°(MD)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Tiny AR	12W	1104	89	2700K	<b>WW27K</b>	<b>CRI80</b>	50°(MD)	White	<b>SWH</b>	Non Dimmable	<b>On/Off</b>
		1141	92	3000K	<b>WW30K</b>	CRI90	62°(WD)	Black	<b>SBL</b>	Phase Dimmable	<b>PDIM</b>
		1203	97	4000K	<b>NW40K</b>			Custom	<b>CSM</b>	Dali Dimmable	<b>DDIM</b>
		1228	99	5700K	<b>CW57K</b>					Bluetooth Dimmable	<b>BTTM</b>
				2700K-5700K	<b>TW</b>						Casambi
				2700K-5700K	<b>TW</b>						
				Warm to Dim	<b>W2D</b>						
<b>Tiny AR</b>	<b>12W</b>				<b>WW27K</b>	<b>CRI80</b>	<b>50°(MD)</b>		<b>SWH</b>		<b>On/Off</b>



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/300mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable