

# Tiny DR | 8W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Remote

LED Power Watts 7.1W

System Power Watts 8.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.95

## Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Tiny DR	8W	WW27K	CRI80	34°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Tiny DR	8W	508	62	2700K	WW27K	CRI80	34°(MD)	White SWH	Non Dimmable On/Off
		525	64	3000K	WW30K	CRI90	47°(WD)	Black SBL	Phase Dimmable PDIM
		549	67	4000K	NW40K			Custom CSM	Dali Dimmable DDIM
		566	69	5700K	CW57K				Bluetooth Dimmable BTTM
						2700K-5700K	TW		
				Warm to Dim	W2D				
Tiny DR	8W			WW27K	CRI80	34°(MD)	SWH	On/off	



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/180mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

