

# Tiny DR | 12W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Aluminium

Primary Lens Polycarbonate

Primary Reflector PC metallised

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 10.7W


System Power Watts 12.3W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/300mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Tiny DR	12W	WW27K	CRI80	44°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL	
Tiny DR	12W	910	74	2700K	WW27K	CRI80	44°(MD)	White	SWH	Non Dimmable	On/Off
		935	76	3000K	WW30K	CRI90	52°(WD)	Black	SBL	Phase Dimmable	PDIM
		984	80	4000K	NW40K			Custom	CSM	Dali Dimmable	DDIM
		1009	82	5700K	CW57K					Bluetooth Dimmable	BTTM
						2700K-5700K	TW				Casambi
				Warm to Dim		W2D					
Tiny DR	12W			WW27K		CRI80	44°(MD)	SWH		On/Off	