

Tiny Wash V2 | 5W

Product Reference

Environment Indoor
 Installation Ceiling Recess

Construction & Materials

Housing Aluminium
 Primary Lens PMMA
 Primary Reflector -
 Secondary Reflector -
 Body Finish White,Black,Custom
 Diffuser -
 Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
 Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed Asymmetric
 Tilt No
 Swivel No

Electrical System


Driven with Constant Current Driver
 Input Voltage/Hz 220V- 240V/50-60Hz
 Control Gear Included
 Mounting Remote
 LED Power Watts 3.6W
 System Power Watts 4.5W
 Operating Voltage Vin 220-240 Vac
 Power Factor p.f. > 0.5

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Tiny Wash V2	5W	WW27K	CRI80		SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL		
Tiny Wash V2	5W	392	87	2700K	WW27K	CRI80	White	SWH	Non Dimmable	On/Off
		405	90	3000K	WW30K		Black	SBL	Phase Dimmable	PDIM
		423	94	4000K	NW40K		Custom	CSM	Dali Dimmable	DDIM
		432	96	5700K	CW57K				Casambi	CBTM
Tiny Wash V2	5W			WW27K	CRI80		SWH	On/Off		



Light Distribution



LED Technology

Binning 3 Step MacAdam
 LED Life Time @ L70/B10 >50000 hours
 Colour Rendering (CRI) CRI80,CRI90
 Led Type COB
 LED Fitted CREE COB LED 9Vdc/350mA

Controls

Standard Switchable On/Off
 Optional PDIM,DDIM,CASAMBI,Non Dimmable