

Go Pro 50 TT | 20W

Product Reference

Environment Indoor
Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium
Primary Lens PMMA
Primary Reflector -
Secondary Reflector Anodised
Body Finish White,Black
Diffuser -
Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium
Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed
Tilt No
Swivel No

Electrical System


Driven with Constant Current Driver
Input Voltage/Hz 220V- 240V/50-60Hz
Control Gear Included
Mounting Remote
LED Power Watts 17.4W
System Power Watts 20.0W
Operating Voltage Vin 220-240 Vac
Power Factor p.f. > 0.95

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Go Pro 50 TT	20W	WW27K	CR180	24°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Go Pro 50 TT	20W	1880	94	2700K	WW27K	24°(SS)	White SWH	Non Dimmable On/Off
		1940	97	3000K	WW30K	32°(MD)	Black SBL	Phase Dimmable PDIM
		2040	102	4000K	NW40K	36°(WD)		Dali Dimmable DDIM
		2080	104	5700K	CW57K	46°(VWD)		Bluetooth Dimmable BTM
				2700K-5700K	TW			Casambi CBTM
					Warm to Dim W2D			
Go Pro 50 TT	20W			WW27K	CR180	24°(SS)	SWH	On/Off



Light Distribution



LED Technology

Binning 3 Step MacAdam
LED Life Time @ L70/B10 >50000 hours
Colour Rendering (CRI) CR180,CR190
Led Type COB
LED Fitted CREE COB LED 36Vdc/500mA

Controls

Standard Switchable On/Off
Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable