

Go Pro 70 TT | 36W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 31.4W


System Power Watts 36.1W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/900mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|--------------|------|-------|-------|---------|--------|---------|
| | Go Pro 70 TT | 36W | WW27K | CRI80 | 22°(SS) | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | | CRI | ANGLE | FINISH | | CONTROL | |
|--------------|------|-------|----------|-------------|-------|--------------------|---------------|--------|-----|----------------|--------|
| Go Pro 70 TT | 36W | 2888 | 80 | 2700K | WW27K | CRI80 | 22°(SS) | White | SWH | Non Dimmable | On/Off |
| | | 2960 | 82 | 3000K | WW30K | CRI90 | 40°(MD) | Black | SBL | Phase Dimmable | PDIM |
| | | 3105 | 86 | 4000K | NW40K | 52°(WD) | Dali Dimmable | | | DDIM | |
| | | 3177 | 88 | 5700K | CW57K | Bluetooth Dimmable | BTTM | | | | |
| | | | | | | 2700K-5700K | TW | | | Casambi | CBTM |
| | | | | Warm to Dim | | W2D | | | | | |
| Go Pro 70 TT | 36W | | | WW27K | CRI80 | 22°(SS) | SWH | On/Off | | | |